




Introduction

Contents


Specifications	2
Straight Cable Plugs	3
Right Angle Cable Plugs	3
Straight Cable Jacks	3
Bulkhead Cable Jacks	3
Panel Cable Jacks	3
Bulkhead Receptacles	4
Panel Receptacles	4
Adapters Within Series	4

MHV Mating Interface Options


Standard—2-Stud mating




Polarized—2-Stud mating



Anti-Rock—3-Stud mating



Anti-Rock—4-Stud mating



MHV series connectors are high-voltage, miniature connectors, with a frequency range of DC–50 MHz and non-constant impedance, designed to MIL-PRF-39012 requirements.

They are similar in size to BNC series but do not mate with BNC connectors.

Their bayonet-type interface provides for quick mating and unmating, and prevents accidental disconnection from pulling forces on the cable.

MHV connectors have deeply-recessed contacts and overlapping insulators for safety in high-voltage applications

Automatic MHV cable connectors have V-Groove cable attachment as standard, but are also available with other cable attachment types:

- Standard and Improved **Wedge-Lock**; our patented, quick assembly method for flexible cable incorporating a captive center contact, only three parts to handle, and requiring no special tools.
- **Econo-Crimp** types with captive or noncaptive contacts for flexible cable, providing small size, light weight, and rapid assembly using standard, commercially-available crimp tools.
- **X-Crimp** with captive contacts for flexible cable, providing rugged, high-strength cable attachment and quick assembly.
- **Wedge-Eze** for flexible cable is our unique system featuring quick assembly, color coding by cable size, and field replaceability. Rapidly assembled with hand or automated tooling.
- **Solder-Clamp** assembly for semi-rigid cable requires no special tools and allows for re-orientation of the connector after assembly to easily conform to system layout. Collet type clamping for solderless attachment of semi-rigid cable is also available.

See the glossary pages beginning on page 6 for details on all cable attachment types.

The versatility of MHV series RF connectors is enhanced by Automatic's ability to provide a wide range of alternate constructions and configurations to meet virtually any system requirements. Contact us with your requirements for custom configurations, such as:

- **Polarized mating interfaces** with reversed contacts and insulators to prevent accidental mating of incompatible circuits. (see illustration at left).
- **Anti-Rock mating interfaces** with three-stud or four-stud designs. (see illustration at left).
- MHV connectors with **aluminum bodies** can provide significant weight savings.

Notes:


The standard MHV connectors in this section have silver-plated bodies and gold-plated center contacts. All are available with other platings if required.

Drawings in this section are approximately actual size; some drawing proportions may be altered to better illustrate details.

Drawing dimensions are in inches (millimeters), based on one inch = 25.4 mm.

Interface Dimensions and Specifications


Interface Dimensions (MIL-STD-348)



Jack Interface

Dim.	Min.	Max.
A	.432 (11.0)	.436 (11.1)
B	.378 (9.6)	.382 (9.7)
C	.319 (8.1)	.321 (8.2)
D	—	.186 (4.7)
E	.327 (8.3)	.335 (8.5)
F	.289 (7.3)	.311 (7.9)
G	.253 (6.4)	.280 (7.1)
H	.075 (1.9)	.081 (2.1)
J	.270 (6.9)	—

Dim.	Min.	Max.
K	.081 (2.1)	.091 (2.3)
L	.346 (8.8)	.356 (9.0)
M	.327 (8.3)	.333 (8.5)
N	.015 (.4)	.030 (.8)
P	.284 (7.2)	.290 (7.4)
R	.086 (2.2)	—
T	.165 (4.2)	.169 (4.3)



Plug Interface

Dim.	Min.	Max.
A	.385 (9.8)	.390 (9.9)
B	To meet gauge test	
C	.278 (7.1)	.282 (7.2)
D	.190 (4.8)	.194 (4.9)
E	.052 (1.3)	.054 (1.4)
F	.207 (5.3)	—
G	.089 (2.2)	.091 (2.3)
H	—	.005 (.1)
J	—	.086 (2.2)

Dim.	Min.	Max.
K	.300 (7.6)	—
M	.302 (7.7)	—
N	.091 (2.3)	.097 (2.5)
P	.394 (10.0)	.400 (10.2)
Q	.124 (3.2)	—
R	.091 (2.3)	.097 (2.5)
S	.463 (11.8)	.473 (12.0)

Specifications (MIL-PRF-39012; MIL-STD-202 test methods)

Electrical:

Frequency Range: DC–50 MHz.

Impedance: Non-constant.

Voltage Rating: 3,500 V RMS; 5,000 V DC.

Insulation Resistance: 5,000 megohms min. (Method 302, condition B).

Dielectric Withstanding Voltage: 5,000 V RMS min. (Method 301).

Environmental:

Vibration: Method 204, Condition A.

Shock: Method 213, condition I.

Temperature Range: -65° to 165°C.

Corrosion: Method 101, condition B.

Mechanical:

Force to Engage and Disengage: Longitudinal force, 3 pounds max.
Torque, 2.5 inch-pounds max.

Coupling Proof Torque: 15 inch-pounds, min.

Coupling Nut Retention: 100 pounds.

Cable Retention: Dependent upon cable; see MIL-PRF-39012 specification sheet.

Mating Characteristics: Per MIL-STD-348.

Durability: 500 mating cycles @ 12 cycles per minute max.

Center Contact Retention: 6 pounds min. axial force (captive-contact types).

Materials (unless otherwise noted):

Male Center Contacts, Plug Outer Contacts: Brass.

Female Center Contacts: Beryllium copper.

Bodies and Other Metal Parts: Brass.

Crimp Sleeves: Annealed brass or soft copper.

Insulators: Teflon (TFE).

Gaskets: Silicone rubber.

Plating:

Center Contacts: Gold plated per current MIL-PRF-39012 requirements.

Other Metal Parts: Silver plated per current MIL-PRF-39012 or MIL-PRF-55339 requirements.

Note: These specifications are typical, and may not apply to all configurations. Specifications may change as MIL specifications are updated.




Cable Plugs and Jacks

Cable Group	Straight Plug—V-Groove		
	Non-captive Contact	Captive Contact	Figure
CF-5, 6	100-M1000A	101-M1100A	1
CF-7, 8	150-M1000A	151-M1100A	1
CF-9	120-M1000A	121-M1100A	1

Cable Group	Straight Jack—V-Groove		
	Non-captive Contact	Captive Contact	Figure
CF-5, 6	100-M3000A	101-M3100A	3
CF-7, 8	150-M3000A	151-M3100A	3
CF-9	120-M3000A	121-M3100A	3

Cable Group	Bulkhead Jack—V-Groove		
	Non-captive Contact	Captive Contact	Figure
CF-5, 6	100-M3000A-81	101-M3100A-81	4
CF-7, 8	150-M3000A-81	151-M3100A-81	4
CF-9	120-M3000A-81	121-M3100A-81	4

Cable Group	Panel Jack—V-Groove			
	Flange	Non-Captive contact	Captive Contact	Figure
CF-5, 6	10	100-M3000A-10	101-M3100A-10	5
	15	100-M3000A-15	101-M3100A-15	
CF-7, 8	10	150-M3000A-10	151-M3100A-10	5
	15	150-M3000A-15	151-M3100A-15	
CF-9	10	120-M3000A-10	121-M3100A-10	5
	15	120-M3000A-15	121-M3100A-15	



Flange Sizes				
Flange #	A	B	C	
10	.69 (17.5)	.50 (12.7)	3-56 tap	
15	.75 (19.1)	.53 (14.0)	ø.13 (3.3)	

- All items have silver-plated bodies and gold-plated contacts. For nickel-plated body, add K at beginning of part number. For gold-plated body add G at beginning of part number.
- See page 5 for cable groups. Most types available for other cables not shown above.
- See pages YY–YY for complete descriptions and illustrations of cable attachment types.

Cable Group	Right Angle Plug—V-Groove	
	Part Number	Figure
CF-5, 6	101-M2100A	2
CF-7, 8	151-M2100A	2
CF-9	121-M2100A	2




Figure 1




Figure 2




Figure 3




Figure 4

*Mounting hole dimensions




Figure 5

Bulkhead and Panel Mounted Receptacles; Adapters Within Series









Bulkhead Jack Receptacles					
Figure	Mounting	Dim. A	Dim. B	Max. Panel	Part Number
1	75	.52 (13.2)	.48 (12.2)	.17 (4.3)	75-M3000
2	60	.39 (30.2)	.35 (8.9)	.09 (2.3)	60-M3000

Panel Jack Receptacles			
Figure	Flange	Max. Panel	Part Number
3	10	.20 (5.1)	10-M3000
3	15	.20 (5.1)	15-M3000

Adapters			
Type	Figure	Part Number	
Jack-Jack	4	M3000	
Jack-Jack, panel mounted (#10 flange)	5	M3000-10	
Jack-Jack, panel mounted (#15 flange)	5	M3000-15	
Jack-Plug, right angle	6	M2100	
Jack-Plug-Jack, tee	7	M7200	

• All items have silver-plated bodies and gold-plated contacts. For nickel-plated body, add K at beginning of part number. For gold-plated body add G at beginning of part number.

Flange #	Flange Sizes		
	A	B	C
10	.69 (17.5)	.50 (12.7)	3-56 tap
15	.75 (19.1)	.53 (14.0)	ø.13 (3.3)



Cable Groups Listed by Cable Type

RG Cables*															
Type	Group	Type	Group	Type	Group	Type	Group	Type	Group	Type	Group	Type	Group	Type	Group
RG-5	CF-13	RG-21	CF-13	RG-58	CF-5	RG-94	CF-33	RG-148	CF-26	RG-180	CF-3	RG-215	CF-23	RG-303	CF-10
RG-6	CF-14	RG-22	TW-2	RG-59	CF-7	RG-108	TW-1	RG-149	CF-26	RG-187	CF-2	RG-216	CF-26	RG-304	CF-12
RG-7	CF-17	RG-30	CF-15	RG-62	CF-7	RG-115	CF-14	RG-150	CF-28	RG-188	CF-2	RG-217	CF-34	RG-307	TR-1
RG-8	CF-22	RG-31	CF-22	RG-63	CF-29	RG-115A	CF-18	RG-156	CF-25	RG-188DS	CF-36	RG-222	CF-13	RG-316	CF-2
RG-9	CF-22	RG-32	CF-23	RG-65	CF-32	RG-116	CF-23	RG-161	CF-2	RG-195	CF-4	RG-223	CF-6	RG-316DS	CF-36
RG-10	CF-23	RG-38	CF-13	RG-71	CF-8	RG-122	CF-9	RG-166	CF-23	RG-196	CF-1	RG-226	CF-35	RG-393	CF-21
RG-11	CF-26	RG-39	CF-14	RG-79	CF-29	RG-140	CF-7	RG-174	CF-2	RG-210	CF-7	RG-227	CF-23	RG-400	CF-6
RG-12	CF-28	RG-41	CF-19	RG-83	CF-20	RG-141	CF-5	RG-174DS	CF-36	RG-212	CF-13	RG-229	CF-23	RG-402	SR-6
RG-13	CF-26	RG-54	CF-15	RG-87	CF-14	RG-142	CF-6	RG-178	CF-1	RG-213	CF-22	RG-235	CF-18	RG-404	CF-1
RG-14	CF-34	RG-55	CF-6	RG-90	CF-16	RG-144	CF-26	RG-179	CF-2	RG-214	CF-22	RG-302	CF-11	RG-405	SR-5

M17 Cables**									
Type	Group	Type	Group	Type	Group	Type	Group	Type	Group
M17/2	CF-14	M17/74-RG215	CF-23	M17/119	CF-2	M17/164	CF-22	M17/184	CF-7
M17/6-RG11	CF-26	M17/75	CF-22	M17/127	CF-21	M17/165	CF-34	M17/185	CF-7
M17/6-RG12	CF-28	M17/77	CF-26	M17/128	CF-6	M17/167	CF-6	M17/186	TW-1
M17/15-RG22	TW-2	M17/78	CF-34	M17/130	SR-6	M17/168	CF-17	M17/187	CF-9
M17/28	CF-5	M17/84	CF-6	M17/132	CF-1	M17/169	CF-1	M17/188	CF-13
M17/29	CF-7	M17/90	CF-8	M17/133	SR-5	M17/170	CF-10	M17/189	CF-23
M17/30	CF-7	M17/92	CF-17	M17/138	CF-2	M17/171	CF-12	M17/190	CF-22
M17/31	CF-29	M17/93	CF-1	M17/151	SR-2	M17/172	CF-2	M17/191	CF-26
M17/45	TW-1	M17/94	CF-2	M17/152	CF-36	M17/173	CF-2	M17/194	CF-6
M17/54	CF-9	M17/95	CF-3	M17/154	SR-1	M17/174	CF-21	M17/195	CF-8
M17/60	CF-6	M17/97	CF-7	M17/155	CF-5	M17/175	CF-6	M17/196	CF-2
M17/62	CF-26	M17/110	CF-11	M17/157	CF-9	M17/180	CF-14	M17/197	CF-6
M17/65	CF-23	M17/111	CF-10	M17/158	CF-6	M17/181	CF-26	M17/198	CF-9
M17/73	CF-13	M17/112	CF-12	M17/162	CF-13	M17/182	TW-2	M17/199	CF-13
M17/74-RG213	CF-22	M17/113	CF-2	M17/163	CF-22	M17/183	CF-6	M17/200	CF-6

Semi-Rigid Cables by Jacket Diameter											
Size	Group	Size	Group	Size	Group	Size	Group	Size	Group	Size	Group
.034"	SR-1	.047"	SR-2	.056"	SR-3	.070"	SR-4	.086"	SR-5	.141"	SR-6


*Unless otherwise noted, cable groups include all variants (A/U, B/U, etc.) of RG types. 'DS' indicates double-shielded version of RG cable.

**Unless otherwise noted, cable groups include all variants of M17 slash sheet indicated.

Construction codes: CF = Coaxial, Flexible; SR = Semi-Rigid; TR = Triaxial; TW = Twinaxial

Cable Attachment Types—Flexible Cable

Standard Wedge-Lock




This patented attachment system features a captive contact, quick assembly, and secure cable retention. The cable braid and jacket are flared over the cone-shaped wedge, and the backnut captures the braid and jacket when screwed into the body assembly.

Unlike some similar constructions, the backnut incorporates a slip ring to prevent twisting of the cable during assembly.

Gaskets in the backnut provide weatherproofing of the cable attachment. The cable center conductor is soldered to the contact.

Many connectors with Wedge-Lock cable attachment are qualified to MIL-PRF-39012, Category A (field replaceable, no special tools required for assembly).

Improved Wedge-Lock



This patented attachment system features a captive contact, quick assembly, and secure cable retention. The cable braid and jacket are flared over the cone-shaped wedge, and the backnut captures the braid and jacket when screwed into the body assembly.

This construction differs from standard Wedge-Lock in that the braid is clamped directly by the nut and wedge, providing metal-to-metal contact. The cable jacket is secured in an adjacent area of the backnut assembly for weatherproofing.

Unlike some similar constructions, the backnut incorporates a slip ring to prevent twisting of the cable during assembly.

The cable conductor is soldered to the contact.


Many connectors with Improved Wedge-Lock cable attachment are qualified to MIL-PRF-39012, Category A (field replaceable, no special tools required for assembly).




Cable Attachment Types—Flexible Cable

Econo-Crimp—Non-Captive Contact

Connector Parts



As Assembled



This inexpensive cable attachment method features quick assembly and small connector size and weight. The cable is stripped and the connector contact soldered to the cable center conductor. The tail of the body is inserted under the cable braid, and the crimp sleeve moved into position and crimped.


For additional savings in assembly time, some Econo-Crimp connectors have contacts that can be crimped to the conductor instead of being soldered.

All Econo-Crimp connectors use readily-available commercial crimp tools and dies for assembly.


Econo-Crimp connectors can be ordered with heat-shrinkable tubing for weatherproofing.

Econo-Crimp—Captive Contact

Connector Parts



As Assembled



These connectors offer quick assembly time and small size, and feature a captive contact which snaps into place in the insulator when assembled. This provides consistent axial contact location within the interface, and prevents movement of the contact from cable flexure or temperature changes after assembly.

The cable is stripped and the connector contact soldered to the cable center conductor. The tail of the body is inserted under the cable braid, and the crimp sleeve moved into position and crimped.

For additional savings in assembly time, some Econo-Crimp connectors have contacts that can be crimped to the conductor instead of being soldered. All Econo-Crimp connectors use readily-available commercial crimp tools and dies for assembly.


Econo-Crimp connectors can be ordered with heat-shrinkable tubing for weatherproofing.

Many connectors with Captive Contact Econo-Crimp cable attachment are qualified to MIL-PRF-39012, Category B (non-field replaceable), Category C (MIL-defined crimp tools and cable strip dimensions), and Category D (MIL-defined contact and crimp-sleeve dimensions).




Cable Attachment Types—Flexible Cable

X-Crimp



X-Crimp cable attachment combines ease of assembly with a captivated contact and a silicone-rubber boot* for weatherproofing. The captive contact is held rigidly in place to prevent movement from cable flexure or temperature changes after assembly. The cable is trimmed, and the tail of the backnut assembly is pushed under the braid. The contact is soldered to the cable conductor, the braid crimped within the crimp sleeve, and the backnut assembly screwed into the body. The boot slides forward and snaps into place. The boots can be supplied in a variety of colors for identification. Some connectors with X-Crimp cable attachment are qualified to MIL-PRF-39012, Category B (non-field replaceable), and Category C (MIL-defined crimp tools and cable stripping dimensions). *SMA and smaller size connectors use heat-shrink tubing instead of silicone-rubber boots.

Wedge-Eze




This unique attachment system provides very fast assembly and is field replaceable. The cable is stripped, and the connector contact soldered to the center conductor. The prepared cable is pushed into the body assembly, and the wedge flares the braid. The plastic wedge cap is pushed forward over the cable braid, where it locks into place. The cap can be assembled with an inexpensive hand tool or using automated equipment for large production runs. The plastic caps can be supplied in a variety of colors for identification.




Cable Attachment Types—Flexible Cable

V-Groove—Non-Captive Contact

Connector Parts



As Assembled



V-Groove cable attachment is the standard for military UG-type connectors, and is field-replaceable with no special tools.


The cable is stripped, and the braid is combed out and folded back over the ferrule. The connector contact is soldered to the cable conductor.

The prepared cable, the V-gasket, and the slip washer are secured in the body assembly by tightening the backnut.


The slip washer prevents twisting the cable while the nut is being tightened, and the rear surface of the ferrule cuts through the V-gasket, providing metal-to-metal braid clamping as well as weatherproofing.

V-Groove—Captive Contact

Connector Parts



As Assembled



V-Groove clamping with a captive contact provides consistent axial contact location within the interface, and prevents movement of the contact from cable flexure or temperature changes after assembly.

The cable is stripped, and the braid is combed out and folded back over the ferrule. The connector contact is soldered to the cable conductor.

The prepared cable, the rear insulator and captivating washer, the V-gasket, and the slip washer are secured in the body assembly by tightening the backnut.


The slip washer prevents twisting the cable while the nut is being tightened, and the rear surface of the ferrule cuts through the V-gasket, providing metal-to-metal braid clamping as well as weatherproofing.

Many connectors with Captive Contact V-Groove cable attachment are qualified to MIL-PRF-39012, Category A (Field replaceable, no special tools required for assembly).



Cable Attachment Types—Semi-Rigid Cable

Solder-Clamp (Used on BNC and larger connectors)



This attachment method is similar to the V-Groove type used for flexible cable, but is adapted to use with semi-rigid cable by replacing the braid-clamp ferrule with a ferrule designed to be soldered to the jacket (outer conductor) of semi-rigid cable.

This design allows right-angle or chassis-mounted connectors to be re-oriented after cable attachment to easily conform to system layout.

The cable is stripped, and the ferrule is soldered to the cable jacket before soldering the contact to the cable conductor. This allows for trimming the cable dielectric after soldering the jacket, eliminating any dielectric extrusion that may occur during jacket soldering.

Captive contacts (as shown) are highly recommended for connectors used with semi-rigid cable.